



XP-350B/350BM

Thermal Barcode Printer

- Compact and space saving design
- Easy paper load with adjustable paper guide
- Printing speed up to 152mm per second
- Max 80mm label diameter, external amount
- and board option
- USB+Serial+ethernet all in one interface
- Thermal sensitive resistance, photoelectric sensor
- black mark sensor

APPLICATIONS



Shopping



Mart



Hospital



Coffee Shop



Restaurant



Ticketing




Express



Factory

XP-350B/350BM

Desktop Barcode Printer



Printing Features		XP-350B	XP-350BM
Resolution	203 DPI (8 dots/mm)		
Printing method	Direct Thermal		
Max.print speed	152mm/s		
Max.print width	Max.76 mm		
Media			
Media type	Thermal paper/Thermal stickers paper		
Media width	20~82 mm		
Media thickness	0.06 ~ 0.19 mm		
Media roll diameter	Max.100 mm		
Performance Features			
Memory	DRAM:4M FLASH:4M		
Interfaces	USB+Serial	USB+Serial+Lan	
Sensors	Print head temperature sensor / Cover open / Paper end / Gap		
Drawer port	1 ports (Pin 2 for cashdrawer)		
Fonts/Graphics/Symbologies			
Character sizes	Font 0 to Font8		
1D barcode	CODE128 / EAN128 / ITF / CODE39 / CODE39C / CODE39S / CODE93 / EAN13 / EAN13+2 / EAN13+5 / EAN8 / EAN8+2 / EAN8+5 / CODABAR / POSTNET / UPC-A / UPCA+2 / UPCA+5/ UPCE / UPCE+2 / UPCE+5 / MSI / MSIC / PLESSEY / ITF14 / EAN14		
2D bar code	PDF417 / QR CODE / DATMATRIXTSPL		
Emulaion	TSPL	ESC/POS	
Physical Features			
Dimension	220*148*150mm (D×W×H)		
Weight	1.44 kg		
Reliability			
Print head life	100 km		
Software			
Driver	Windows / Linux / Mac / Android		
Power supply			
Input	DC 24V/2.5A		
Environmental Conditions			
Operation	5 ~ 45℃, Humidity:20 ~ 80%RH		
Storage environment	-40 ~ 55 ℃, Humidity: ≤93%RH(40℃)		



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
Email: overseas@xprinter.net

