

Impact Dot matrix Printer




XP-76IIN

- Support GB18030
- Three-ply capable
- Black mark orientation
- Bi-directional printing



XP-76IIN

Impact Dot matrix Printer



Printing		XP-76IIN
Printing method	9-Pin serial impact dot-matrix printing	
Printing width	63.5mm	
Print Resolution	84 dpi	
Printing speed	4.5 line/s	
Interface	Parallel/USB	
Print paper	75.5±0.5mm Φ65mm	
Character size	ANK, Font A: 1.6×3.1mm (9×9 dots) Font B: 1.2×3.1mm (7×9 dots) Chinese, traditional Chinese: 2.7×2.7mm (16×16 dots)	
Column number	Font A - 33 columns /Font B - 40 columns / Chinese, traditional Chinese - 22 columns	
Character		
Extension character sheet	PC437/Katakana/PC850/PC860/PC863/PC865/WPC1252/PC866/PC852/PC858	
Software		
Driver	Windows /Linux /Mac	
Utility	Windows	
SDK	Windows/ Android	
Power		
Power adaptor	Input: AC 110V/220V, 50 ~ 60Hz, Output: DC 24V/2.5A	
Printer input	DC 24V/2.5A	
Cutter		
Auto cutter	Partial	
Physical characteristics		
Weight	1.46KG	
Dimensions	230*150*138mm (D×W×H)	
Environmental Requirements		
Work environment	0 ~ 45℃, 10 ~ 80% RH	
Storage environment	-10 ~ 60℃, 10 ~ 90% RH (no condensation)	
Reliability		
Printer head life	10 Million Lines	
Cutter life	1 Million	



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
Email: overseas@xprinter.net

