

XP-MP12

Panel Printer



Key features

- Mini size, light and multi-functions
- Easy to operate and connect
- Fast speed, high quality and stylish appearance

Applications



Shopping



Mart



Restaurant



Hospital




CoffeeShop



Ticketing

XP-MP12

Panel Printer



Printing		XP-MP12
Printing method	Direct thermal	
Print width	48 mm	
Column capacity	384 dots/line	
Printing speed	90 mm/s	
Interface	USB+Serial	
Paper width	58mm 60mm	
Character size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots)	
Line spacing	Chinese, traditional Chinese:3.0×3.0mm (24×24 dots) 3.75 mm	
Barcode Character		
Extension character sheet	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)	
Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
Input buffer	32k bytes	
NVFlash	64k bytes	
Power		
Power source	Output:DC 12V/2.6A	
Cash drawer output	DC 12V/1A	
Physical characteristics		
Weight	0.295 KG	
Dimensions	132*125.5*83.1mm (D×W×H)	
Environmental Requirements		
Work environment	Temperature: 0~45℃ humidity : RH 10 ~ 80%	
Storage environment	Temperature: -10~60℃ humidity: RH 10~90℃	
Reliability		
Printer head life	50 KM	



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

