

Thermal Transfer / Direct Thermal


XP-TT425B

- Faster printing speed, 6 inches 152mm/s, to improve the daily efficiency.
- A new generation printhead is applied to enhance the printing quality.
- 8MB SDRAM & 8MB Flash memory for a more flexible usage.
- Rich emulation language compatibility: TSPL, ZPL, EPL, DPL.
- 300m ribbon capacity design.



XP-TT425B

Thermal Transfer/ Direct Thermal



Printing Features		XP-TT425B	
Resolution	203 DPI		
Print method	Thermal Transfer / Direct Thermal		
Max.Print speed	152 mm (6") / s		
Max.print width	104 mm (4.09")		
Max.print length	1778 mm (70")		
Media			
Media type	Continuous, gap, black mark, fan-fold and punched hole		
Media width	25.4-118mm (1.0"-4.6")		
Media thickness	0.06~0.254 mm (2.36~10mil)		
Media core diameter	25.4 ~ 76.2 mm (1 " ~ 3 ")		
Label length	10 - 1778 mm(0.39" ~ 70")		
Label roll capacity	127 mm (5") OD (external diameter)		
Ribbon capacity	Max.300m		
Ribbon width	110m		
Performance Features			
Processor	32-bit CPU		
Memory	8MB Flash Memory/ 8MB SDRAM/ Flash memory can be expanded Max.4Gb		
Interface	Standard:USB TF card Optional: Lan/WIFI/Bluetooth/Serial		
Sensors	① Gap sensor ② Cover opening sensor ③ Black mark sensor ④ Ribbon sensor		
Fonts/Graphics/Symbologies			
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.		
1D barcode	Code 39, Code 93, Code 128UCC, Code 128 , subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11		
2D barcode	PDF-417, Maxicode, DataMatrix, QR code		
Rotation	0°、90°、180°、270°		
Emulaion	TSPL、EPL、ZPL、DPL		
Physical Features			
Dimension	302.5 mm (D) x 234 mm (W) x 195.18 mm (H)		
Weight	2.7 kg		
Reliability			
Print head life	30 km		
Software			
Driver	Windows / Linux / Mac		
SDK	Windows / Android / iOS		
Power supply			
Input	AC 100-240V,1.8A, 50-60Hz		
Output	DC 24V, 2.5A, 60W		
Options			
Factory Options	① Built-in Ethernet server (10/100 Mbps); ② RS-232C (2400-115200 bps) communication interface; ③ WiFi module ④ Cutter ⑤ Bluetooth module(RS-232C communication interface)		
Dealer Options	① External paper roll holder and 1 "paper roll ② Extension board for external paper roll holder		
Environmental Conditions			
Operation	5 ~ 40°C(41~104°F) , Humidity: 25 ~ 85% non-condensing		
Storage environment	-40 ~ 60°C(-40~140°F) . Humidity:10 ~ 90% non-condensing		



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

